



# AQUOLAC PAINTS

## AQUARUB CHLORINATED RUBBER PAINT



AQUARUB Chlorinated Rubber paint is manufactured by using carefully selected pigments and chemicals in plasticised Chlorinated Rubber media. It is chemically unreactive and shows a high degree of impermeability to water and water vapours. It protects the surfaces subjected to highly humid, salty and corrosive atmospheric conditions, and also protect the surface from acidic vapours or light acid attack. AQUARUB provides antifungus properties and has very good drying characteristics, flexibility and hardness.

**Uses:** AQUARUB can be applied on all types of steel structure, equipment's, chemical plants, Fertilizer plants, garages, Sackers and sewage disposal plants, can also be used floors, Walls and swimming pools.

**Application :** Can be applied by spray or Brush. To obtain best results two to three coats should be applied.

**Finish :** Smooth, Hard and Glossy/S.Glossy.

**Drying Time :**

SURFACE DRY : 20 Minutes

HARD DRY : 4- 6 Hours

**Packing :** 20 LTRS. / 4 LTRS.

**Precautions :**

1. Avoid over brushing
2. Proper ventilation must be provided in confined space.
3. No smoking or naked flame should be allowed in the Painting area.
4. Ensure satisfactory drying before the application of second coat.