

## **ACRYLIC COATINGS**

### *For Exterior Finish*

#### Product Description

A high quality modified acrylic emulsion pigmented with titanium dioxide and other light fast and alkali resisting pigments. It has good flow and leveling and colour retention properties. It is an ideal smooth and matt coating for external areas.

#### Recommended Areas of Application:

Area of use : Exterior & Interior  
Substrate : Concrete, plaster, masonry, brickwork, blockwork

#### Technical Data:

Sheen Variants : Matt & Smooth  
Colours : As per shade card.

#### Theoretical Covering Capacity

Recommended Dry Film Thickness Per Coat : 40 microns (typical)  
Theoretical Spread Rate : 7 m<sup>2</sup> / Ltr.

Drying Time : Touch Dry – 1 Hour  
Interval Between 2 Coats : 5 - 6 Hours

#### Application Data:

Method of Application : Brush, Roller, or Spray Application.  
Thinner : Sweet Water  
Thinning Ratio (by vol.) : Use 15% to 20% maximum for ease of application depending on the method of application.

### Surface Preparation:

The performance of this coating is directly related to the degree of surface preparation.

- Ensure the surface is clean, dry, and free from all contaminants.
- Surface must be sound and free from laitance.
- Remove laitance by wire brush or sweep blast.

### Application Details:

- Ensure adequate ventilation during application and drying.
- Do not apply During Rain
- Stir the contents thoroughly before and during the use, with a broad flat stirrer, using an upward lifting action.

**Brush or Roller** : Apply an even coat taking care to avoid runs and sags. Minimum two coats recommended.

**Conventional Spray** : Use normal spray equipment

### Storage, Safety Information and Precautions:

- Keep out of reach of children.
- Store in cool, dry conditions; ensure adequate ventilation during application.
- Shelf life up to 24 months from the date of manufacture.
- Avoid contact with skin and eyes; wear suitable protective clothing such as overalls, goggles, dust masks and gloves.
- Flash Point : NA

### Precautions:

- **Eyes:**  
In the event of accidental splashes, flush eyes immediately with warm water and obtain medical advice.
- **Skin:**  
Wash skin thoroughly with soap and water, or with an approved industrial cleaner. Do not use solvents.
- **Inhalation:**  
Move patient to fresh air, loosen collar and keep patient rested.
- **Ingestion:**  
Do not induce vomiting. Obtain immediate medical attention.
- **Dispose in landfill only.**

**Packaging Size:**

1, 4, 10 and 20 Ltr.

**Disclaimer:**

The information provided in this data sheet is not intended to be complete. It is the responsibility of the user to ensure that the product used is suitable for the purpose it is meant to serve. In view of various factors affecting the performance of the coating, we cannot assume responsibility for the product performance, nor do we accept any liability arising from use of this product, unless specifically agreed to in writing by us. The information provided in the datasheet may be modified by us without notice

