

AQUOLAC DAMP-STOP

High Quality Elastomeric Waterproofing Membrane

Product Description

Aquolac damp-stop is a special synthetic resin based waterproofing coatings. Because of its excellent flexibility and thixotropic nature, it is ideal for use on vertical as well as horizontal surface. It is a single pack, very economical and pollution-free coatings. Due to its white colour, it offers excellent UV resistance and solar reflectivity. Give cooling effect due to the reflective properties.

Direction for use:

1. Prepare the surface by cleaning and ensuring that it is free of dust, oil, grease, grime, and loose particles.
2. Dilute 1 ltr. of Aquolac damp-stop with 1.5 ltr. to 2 ltr. of water and apply it as a primer coat.
3. Apply 2 coat of Aquolac damp-stop after drying of primer coat.
1st coat - dilute it upto 20% (with water)
2nd coat - dilute it upto 10% (with water)
4. Apply it by brush, roller and sprayer.
5. Don't apply during rain or high temperature.
6. Allow it to dry minimum 4-6 hour between 2 coats.

Coverage:

Approximate coverage of Aquolac damp-stop for 1 coat primer + 2 coats is around 18 - 20 sq. Ft. / ltr.

For re-painted wall - on previously painted surface with exterior paint, apply Aquolac damp-stop by diluting it up to 10% (with water) , it will cover surface around 30-40 sq. Ft. / ltr. Depending upon surface.

Usage:

Effective on all exterior surface like terrace, chajjas , vertical walls , etc.

Storage:

Keep it in a cool place away from direct sunlight and high temperature.

Packaging:

5, 10 & 20 Ltr.

