

## **ARCO DAMP - CURE**

### **High Quality Elastomeric Waterproofing Membrane**

**ARCO DAMP - CURE** is a special synthetic resin based waterproofing coating. Because of its excellent flexibility and thixotropic nature, it is ideal for use on vertical as well as horizontal surface. It is a single pack, very economical and pollution-free coatings. Due to its white color, it offers excellent UV resistance and solar reflectivity. Give cooling effect due to the reflective properties.

#### **DIRECTIONS FOR USE**

1. Prepare the surface by cleaning and ensuring that it is free of dust, oil, grease, grime and loose particles.
2. Dilute 1 ltr. of **ARCO DAMP - CURE** with 1.5 ltr. to 2 ltr. of water and apply it as a primer coat.
3. Apply 2 coats of **ARCO DAMP - CURE** after drying of primer coat.  
**1st coat** - dilute it up to 20% (with water)  
**2nd coat** - dilute it up to 10% (with water)
4. Apply it with brush, roller and sprayer.
5. Don't apply it during rain or high temperature.
6. Allow it to dry minimum 4-6 hours between 2 coats.

#### **COVERAGE**

Approximate coverage of **ARCO DAMP - CURE** for 1 coat primer + 2 coats is around 18 - 20 sq. Ft. / ltr.

**For Re-painted Wall:** On previously painted surface with exterior paint, apply **ARCO DAMP - CURE** by diluting it up to 10% (with water) , it will cover surface around 30-40 sq. Ft. / ltr. depending upon surface.

Effective on all exterior surface like terrace, chajjas, vertical walls, etc.

#### **STORAGE**

Keep it in a cool place away from direct sunlight and high temperatures.

#### **PACKAGING**

20, 10 and 5 ltr.

