

AQUOLAC FIBER MESH ROLL (GLASS WOVEN FABRIC)

Description

Fiber Glass Mesh is a ready-to-use mesh which is thin, strong and flexible alkali resistant for embedment with waterproofing and crack-isolation membrane on both the residential and commercial floors & walls of sunk portions and top roof terrace. Fiber Glass Mesh improves the performance of building near water bodies when applied over cracks, coves and corners and around drains

Advantages

- Durable and flexible
- Easy embedment
- Easy in installation
- Ready to use
- Easy to cut with knife or scissors

Uses

- In kitchen wash area
- Terrace or roof area
- Areas near water bodies where hydrostatic pressure exist
- To repair patches of floors, ceiling and rendering walls
- Toilet bathroom and sunken portion



Process of application

After applying first layer of waterproofing as per the requirements by using appropriate equipment. Lying of the net over the first coat of the application done, positioning it in the vertical or horizontal directions and overlapping the joints by at least 10 cm. Level the surface properly It is advisable to add strips of net sloping at 45° on a level with windows and door openings. If waterproofing integrity is required in expansion and control joints net strip can be bond on two sides of joint and seal it.

Technical Information

PROPERTIES	RESULTS
Appearance	White colour glass fiber
Weight	50 gm/meter square
Thickness	0.012"(0.3mm)
Weave	Leno
Application temperature	-20°C to +45°C

Benefits

- Compatibility: It has excellent compatibility with all cement- or epoxybased mortars.
- User friendly: specifically developed to provide an easy to apply product.
- Definable performance: positive benefits are easily demonstrated via a single and simple measurement

Packaging

• Fiber Glass Mesh is supplied in 50 meters & 100 meters rolls

Storage

• Minimum of 2 years shelf-life if kept under room temperature (i.e. 27°C).It should kept away from direct sunlight and store in cool and dry place.