



AQUACRETE DAMP-STOP

HIGH QUALITY ELASTOMERIC WATERPROOFING MEMBRANE

DESCRIPTION

Aquacrete damp-stop is special synthetic resin based waterproofing coatings. Because of its excellent flexibility and thixotropic nature it is ideal for use on vertical as well as horizontal surface. It is a single pack, very economical and pollution free coatings. Due to its white colour, it offers excellent UV resistance and solarreflectivity. Give cooling effect due to the reflective properties.

Direction for use

1. Prepare the surface by cleaning and ensuring that it is free of dust , oil , grease , grime and loose particles.
2. Dilute 1 ltr. Of Aquacrete damp-stop with 1.5 ltr. to 2 ltr. Of water , and apply it as a primer coat .
3. Apply 2 coat of Aquacrete damp-stop after drying of primer coat .
1st coat – dilute it upto 20% (with water)
2nd coat – dilute it upto 10% (with water)
4. Apply it by brush , roller and sprayer .
5. Don't apply during rain or high temperature.
6. Allow it to dry minimum 4-6 hour between 2 coats.



COVERAGE

Approximate coverage of Aquacrete damp-stop for 2 coat application is around 20-25 sq. Ft. / ltr.

For re-painted wall – on previously painted surface with exterior paint , apply Aquacrete damp-stop by diluting it upto 10% (with water) , it will cover surface around 30-40 sq. Ft. / ltr. Depending upon surface .

Effective on all exterior surface like terrace ,chajjas , vertical walls , etc. Effective on cement sheet, on metal sheet & MS sheet.

Storage

Keep it in a cool place away from direct sunlight and high temperature.

PACKAGING

20LTR. , 10 ltr. 5ltr.

AQUOLAC COATINGS

A-161/162, S.P. Mukherjee Market, Jhandewalan,
Behind Saran Petrol Pump, M.M Road,
(Rani Jhansi Road) New Delhi – 110005.
Ph.: 011-23622889, 23514708
E-mail: info@aquolac.com, Website : www.aquolac.com

